

1.2 – PRODUCT SPECIFICATION TABLE

SOLID FORMS		FORM CAVITY WIDTH				
Product	Feature	4" (102mm)	6.25" (159mm)	8" (203mm)	10" (254mm)	12" (305mm)
Standard	Length	48" (1219mm)	48" (1219mm)	48" (1219mm)	48" (1219mm)	n/a
	o/a width	9.5" (241mm)	11.75" (298mm)	13.5" (343mm)	15.5" (394mm)	n/a
	Height	16" (406mm)	16" (406mm)	16" (406mm)	16" (406mm)	n/a
90° Corner <small>*Dimensions taken from the longer panel</small>	*Length (short leg)	16.125" (410mm)	16.125" (410mm)	16.125" (410mm)	18.5" (470mm)	n/a
	*Length (long leg)	32.125" (816mm)	32.125" (816mm)	32.125" (816mm)	34.5" (876mm)	n/a
	o/a width	9.5" (241mm)	11.75" (298mm)	13.5" (343mm)	15.5" (394mm)	n/a
	Height	16" (406mm)	16" (406mm)	16" (406mm)	16" (406mm)	n/a
45° Corner <small>*Dimensions taken from the longer panel</small>	*Length (short leg)	9.5" (241mm)	9.5" (241mm)	9.5" (241mm)	n/a	n/a
	*Length (long leg)	25.5" (648mm)	25.5" (648mm)	25.5" (648mm)	n/a	n/a
	o/a width	9.5" (241mm)	11.75" (298mm)	13.5" (343mm)	n/a	n/a
	Height	16" (406mm)	16" (406mm)	16" (406mm)	n/a	n/a
Brick Ledge	Length	n/a	48" (1219mm)	48" (1219mm)	48" (1219mm)	n/a
	o/a width	n/a	11.75" (298mm)	13.5" (343mm)	15.5" (394mm)	n/a
	Height	n/a	16" (406mm)	16" (406mm)	16" (406mm)	n/a
Transition Block	Length	n/a	48" (1219mm)	n/a	n/a	n/a
	o/a width	n/a	11.75" (298mm)	n/a	n/a	n/a
	Height	n/a	16" (406mm)	n/a	n/a	n/a
Taper Top	Length	n/a	48" (1219mm)	48" (1219mm)	48" (1219mm)	n/a
	o/a width	n/a	11.75" (298mm)	13.5" (343mm)	15.5" (394mm)	n/a
	Height	n/a	16" (406mm)	16" (406mm)	16" (406mm)	n/a
Double Taper Top	Length	48" (1219mm)	48" (1219mm)	n/a	n/a	n/a
	o/a width	9.5" (241mm)	11.75" (298mm)	n/a	n/a	n/a
	Height	16" (406mm)	16" (406mm)	n/a	n/a	n/a
Pilaster	Length	Field cut up to 10.447" (265mm)	Field cut up to 10.447" (265mm)	Field cut up to 10.447" (265mm)	Field cut up to 10.447" (265mm)	Field cut up to 10.447" (265mm)
	o/a width	21.5" (546mm)	21.5" (546mm)	21.5" (546mm)	21.5" (546mm)	21.5" (546mm)
	Height	16" (406mm)	16" (406mm)	16" (406mm)	16" (406mm)	16" (406mm)
Height Adjuster	Length	24" (610mm)	24" (610mm)	24" (610mm)	24" (610mm)	n/a
	Thickness	2.75" (70mm)	2.75" (70mm)	2.75" (70mm)	2.75" (70mm)	n/a
	Height	4" (102mm)	4" (102mm)	4" (102mm)	4" (102mm)	n/a
End Cap	Thickness	2.25" (57mm)	2.25" (57mm)	2.25" (57mm)	2.25" (57mm)	n/a
	Width	4" (102mm)	6.25" (159mm)	8" (203mm)	10" (254mm)	n/a
	Height	16" (406mm)	16" (406mm)	16" (406mm)	16" (406mm)	n/a

SYSTEM OVERVIEW

1.2 – PRODUCT SPECIFICATION TABLE

CONTINUED

KNOCKDOWN FORMS		FORM CAVITY WIDTH				
Product	Feature	4" (102mm)*	6.25" (159mm)*	8" (203mm)*	10" (254mm)*	12" (305mm)*
Straight panels**	Length	n/a	48" (1219mm)	48" (1219mm)	48" (1219mm)	48" (1219mm)
	o/a width	n/a	11.75" (298mm)	13.5" (343mm)	15.5" (394mm)	17.5" (445mm)
	Height	n/a	16" (406mm)	16" (406mm)	16" (406mm)	16" (406mm)
90° Corner *Dimensions taken from the longer panel	*Length (short leg)	n/a	16.125" (410mm)	16.125" (410mm)	18.5" (470mm)	18.5" (470mm)
	*Length (long leg)	n/a	32.125" (816mm)	32.125" (816mm)	34.5" (876mm)	34.5" (876mm)
	o/a width	n/a	11.75" (298mm)	13.5" (343mm)	15.5" (394mm)	17.5" (445mm)
	Height	n/a	16" (406mm)	16" (406mm)	16" (406mm)	16" (406mm)

**Straight panels include Standard, Brick Ledge, Transition Block, and Taper Top

XRV PANELS		FORM CAVITY WIDTH				
Product	Feature	4" (102mm)*	6.25" (159mm)*	8" (203mm)*	10" (254mm)*	12" (305mm)*
Standard panels	Length	n/a	48" (1219mm)	48" (1219mm)	48" (1219mm)	48" (1219mm)
	o/a width	n/a	Varies***	Varies***	Varies***	Varies***
	Height	n/a	16" (406mm)	16" (406mm)	16" (406mm)	16" (406mm)

***XRV Panels provide Standard form panels that are 4, 5, 6, 7, or 8 inches thick.

HALF-HEIGHT FORMS		FORM CAVITY WIDTH				
Product	Feature	4" (102mm)	6.25" (159mm)	8" (203mm)	10" (254mm)	12" (305mm)
Standard	Length	48" (1219mm)	48" (1219mm)	48" (1219mm)	n/a	n/a
	o/a width	9.5" (241mm)	11.75" (298mm)	13.5" (343mm)	n/a	n/a
	Height	8" (203mm)	8" (203mm)	8" (203mm)	n/a	n/a
90° Corner *Dimensions taken from the longer panel	*Length (short leg)	16.125" (410mm)	16.125" (410mm)	16.125" (410mm)	n/a	n/a
	*Length (long leg)	32.125" (816mm)	32.125" (816mm)	32.125" (816mm)	n/a	n/a
	o/a width	9.5" (241mm)	11.75" (298mm)	13.5" (343mm)	n/a	n/a
	Height	8" (203mm)	8" (203mm)	8" (203mm)	n/a	n/a
45° Corner *Dimensions taken from the longer panel	*Length (short leg)	9.5" (241mm)	9.5" (241mm)	9.5" (241mm)	n/a	n/a
	*Length (long leg)	25.5" (648mm)	25.5" (648mm)	25.5" (648mm)	n/a	n/a
	o/a width	9.5" (241mm)	11.75" (298mm)	13.5" (343mm)	n/a	n/a
	Height	8" (203mm)	8" (203mm)	8" (203mm)	n/a	n/a

FURRING STRIPS	Height (full height forms)	Height (half height forms)	Width	Thickness
	14.25" (362mm)	6.25" (159mm)	1.25" (32mm)	0.188" (4.8mm)

90° CORNER FURRING STRIPS	Height (Vertical Strip)	Height (Horizontal Strip)	Width (Vertical Strip - one side of corner)	Width (Horizontal Strip - one side of corner)	Thickness
	14.25" (362mm)	2" (50mm)	1.875" (48mm)	5.75" (147mm)	0.188" (4.8mm)

SYSTEM OVERVIEW

Good. Solid. Green.™	www.logixicf.com	1 – 6	
-----------------------------	--	--------------	---